



## Unique Polymer Systems – Single Component Solvent Based Waterproofing Coating

**UPS ATWP** is a high performance, simple to use non silicone transparent water repellent system designed for application to masonry surfaces.

**UPS ATWP** is based on a unique blend of water-repellent resins specifically developed to produce a coating which provides up to 10 years repellency on a wide range of masonry surfaces including concrete, asbestos, brickwork, natural and artificial stone without affecting the natural appearance of the surface.

**UPS ATWP** is micro-porous, allowing the masonry to breathe and meets the requirements of BS6477: 1984 for brickwork and limestone surfaces.

**Before proceeding, please read the following information carefully to ensure that the correct application procedure is fully understood.**

### SURFACE PREPARATION

All surfaces should be clean, dry and free from other contamination.

NOTE: If the surface to be treated is wet some white staining may occur after application of **UPS Aqua-Tech W.P.**

Any adjacent painted areas, such as door and window frames should be protected against contact as the **UPS Aqua Tech W.P.** may cause softening of the paint.

### MIXING

**UPS ATWP** is a single component material and should only require stirring prior to use to incorporate any slight separation.

### APPLICATION

**UPS ATWP** should be applied liberally to the prepared surface using pneumatic spray or large paint brush.

Application should start at the highest point of the surface to be treated allowing excess material to drain down the surface.

One coat is sufficient for most surfaces, however on very porous surfaces a second coat should be applied as soon as the first coat is dry.

All equipment should be cleaned **IMMEDIATELY** after use using **UPS Universal Cleaner**.

### Theoretical Coverage Rate

Whilst it is not possible to provide a theoretical coverage rate, in practice coverage varies between 2 and 4 m<sup>2</sup> per litre (21.5 ft<sup>2</sup> and 43 ft<sup>2</sup> per litre) depending on the porosity of the surface.

Detailed working recommendations are available from the Technical Centre on request.

**PHYSICAL CONSTANTS**

**Mixing Ratio** Supplied ready for use.

**Appearance** Water white liquid.

**Drying & Cure times at 20°C (68°F)**

2 - 4 hours depending on prevailing conditions.

**Volume Solids** 7%

**V.O.C.** 783 gm/litre

**Shelf Life** Use within 5 years of purchase.

Store in original sealed containers at temperatures between 10°C (50°F) and 30°C (86°F).

**Water Repellency**

Meets the requirements of BS 6477:1984 for brickwork and limestone surfaces.

**HEALTH AND SAFETY**

In the wet state UPS ATWP is flammable.

Adequate ventilation should be provided in confined areas.

Undue skin contact should be avoided.

Eyes should be protected from splashes by wearing goggles.

A fully detailed Material Safety Data Sheet is either included with the material or is available on request.

**PACKAGING**

Supplied in 5 and 25 litre packs.

The information provided in this Product Data Sheet is intended as a general guide only and should not be used for specification purposes. The information is given in good faith but we assume no responsibility for the use made of the product or this information because this is outside the control of the company. Users should determine the suitability of the product for their own particular purposes by their own tests.

**FOR FURTHER INFORMATION PLEASE CONTACT**



UniquePolymerSystems.com

*The Engineer's Choice*

*... for Solutions*

www.UniquePolymerSystems.com

Quarry House, Hollybush, Ledbury, Herefordshire. HR8 1ET. UK

Tel: +44(0)1531 636300 Fax: +44(0)8700 558801

Email: sales@UniquePolymerSystems.com